

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number
WO 2005/029014 A3(51) International Patent Classification:
H03K 3/00 (2006.01)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:
PCT/IL2004/000873(22) International Filing Date:
21 September 2004 (21.09.2004)(25) Filing Language:
English(26) Publication Language:
English(30) Priority Data:
60/505,024 24 September 2003 (24.09.2003) US

(71) Applicant (for all designated States except US): T Squared Thermal Technologies, Ltd. [IL/IL]; p.o.box 70084, 31700, Haifa (IL).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


Published:

(75) Inventor/Applicant (for US only): BARAK, Menashe [IL/IL]; 26 Leah street, 34403 Haifa (IL).

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: PULSE FORMING NETWORK AND PULSE GENERATOR



(57) **Abstract:** A pulse forming network is disclosed. The device comprising two pulse forming networks (40), a first pulse forming network comprising n sections, n being an integer, and a second pulse forming network comprising m sections, m being an integer, each of the sections of the first and the second pulse forming networks comprising at least one capacitor and at least one inductor, and each pulse forming network having one output port for connecting a load, the two pulse forming networks electrically connected and magnetically coupled back to back. A method and device for extinguishing an electrical pulse generated by a pulse generator is also disclosed (SWo).

WO 2005/029014 A3



(88) Date of publication of the international search report:
15 June 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.